

YTK EDR-N200H 200"16:10 14 feet width

Grand Electric Fiberglass Screen (Full HD)



Features

- Roller Motor , 28 rotational speed of 1 minute(Motor: Three wired, quick reversal type, with thermal overload cutout, Integral gears, capacitor and electric brake to avoid coasting.)
- Preset and adjustable limit switch to stop screen in up/down positions
- Rigid metal roller with bearing.
- Coordination Projector makes Electric Screen automation
- Support RF wireless remote control, Up, Down, stop control switch for remote control



• Color: black/ White

• Category: Matte Fiberglass

• Material: Aluminum alloy + iron

Flame retardant: yesMildew resistant: yes

Black masking borders: yes
The best viewing angle: 160°

• Higher gain better reflection effect: Gain: 1.0

• Upper the shaft material: Aluminum alloy

• Below the shaft material: iron

• 1. Synchronous motor device can make screen work smoothly.

• 2. Streamline design, Beautiful with artistic appearance.

• 3. Manual or remote control is optional. Free to stop the screen at any location.

• 4. The screen surface is smooth and hard to distortion. It is also flame retardant, mildew and in duration resistant.

• 5. Screen surface can be cleaned (mild dishwashing liquid diluted with warm water)

Specification

- Nominal Diagonal: 200" (9.7 feet) 16:10

- Viewing size(W) x (H): inch:170" x 106" / mm: 4308 mm x 2692mm / feet: 14' x 8.8'

- Does not Needs the Horizontal seam

- Covering Material: Metal

- Thickness of casing: 8"

- N.W.(kg): 150

- G.W.(kg): 180

Power Supply: 220 V / 50 ~ 60 Hz

- Covering Dimension(L x W x H)mm: 4650 x 200 x 150

Accessories(Wireless control series):

RF-A1 RF-A2 for EDR-series RF-A3

(Wireless/ relay control) (Built-in install/ (Wireless/manual control)

Wireless/ relay control)









RF-A232
(Wireless/RS232/Manual/relay control)



Suitable use:

Hall, Lecture Theaters, Cinemas

Warranty: 12 Month

CB CE