

YTK ETS198R 4:3 13.2 feet width

Rear Tension Electric Screen (HD/short focus)



Features

• Roller Motor, 28 rotational speed of 1 minute(Motor: Three wired, quick reversal type, with thermal overload cutout, Integral gears, capacitor and electric brake to avoid coasting.)

- Preset and adjustable limit switch to stop screen in up/down positions
- Rigid metal roller with bearing.
- Coordination Projector makes Electric Screen automation
- Support RF wireless remote control, Up, Down, stop control switch for remote control
- Color: black/ Yellow/ White
- Category: Matte Soft (Rear)



- Material: Aluminum alloy + iron
- Flame retardant: yes
- Mildew resistant: yes
- Black masking borders: yes
- \bullet The best viewing angle: 120 $^{\circ}$
- Higher gain better reflection effect: Gain: 1.0
- Upper the shaft material: Aluminum alloy
- Below the shaft material: iron
- 1. Synchronous motor device can make screen work smoothly.
- 2. Streamline design, Beautiful with artistic appearance.
- 3. Manual or remote control is optional. Free to stop the screen at any location.
- 4. The screen surface is smooth and hard to distortion. It is also flame retardant, mildew and in duration resistant.
- 5. Screen surface can be cleaned (mild dishwashing liquid diluted with warm water)

Specification

- Nominal Diagonal: 198" (13 feet) 4:3
- Viewing size(W) x (H): inch:158" x 119" / mm: 4023 mm x 2743mm / feet: 13.2' x 9.9'
- Does not Needs the Horizontal seam
- Covering Material: Aluminum alloy
- Thickness of casing: 7.1"
- N.W.(kg): 68
- G.W.(kg): 73
- Power Supply: 220 V / 50 ~ 60 Hz
- Covering Dimension(L x W x H)mm: 4300 x 180 x 180

Accessories(Wireless control series):

RF-A1

RF-A2 for EDR-series (Built-in install/

Wireless/ relay control)



(Wireless/ relay control)





(Wireless/manual control)

RF-A3



RF-A232 (Wireless/RS232/Manual/relay control)



Suitable use:

Hall, Lecture Theaters, Big Classroom, VIP rooms Warranty: 12 Month

CB CE